

Cover policy for Infiltrator chambers in conventional septic system applications.



INFILTRATOR®
systems inc.

□ The intent of this policy is to establish cover guidelines for maintaining structural integrity.

□ During system design it is important to note that any septic system designed and installed deeper than 4 feet may experience performance problems as a result of limited oxygen transfer through the soil.

□ Depth requirements may vary according to state and local regulations. If unsure of installation requirements, contact your state or local regulators.

□ Questions regarding the installation of Infiltrator chamber systems? Call the Technical Service Department at 1-800-221-4436 for current installation instructions.

Table 1: Burial depth in feet (exclusive of chamber height)

Configuration	Products				
	Quick4 Standard	Quick4 High Capacity	High Capacity H-20	Quick4 Equalizer 24	Quick4 Equalizer 36
minimum cover in feet					
Beds	0.5/1 *	0.5/1 *	1.5	0.5/1 *	0.5/1 *
Trenches **	0.5/1 *	0.5/1 *	1.5	0.5/1 *	0.5/1 *
maximum cover in feet					
Beds	4	4	8	4	4
Trenches **	8	8	8	8	8

* 0.5 feet burial depth for non-traffic applications only. 1.0 feet burial depth for H-10 load rating.

** Trenches refers to a 1-foot minimum soil separation between chamber rows.



INFILTRATOR®
systems inc.

P.O. Box 768 • 6 Business Park Road • Old Saybrook, CT 06475
860-577-7000 • FAX 860-577-7001

www.infiltratorsystems.com

1-800-221-4436

Distributed By: